



PRODUCT SPECIFICATIONS



SPEEDY BLUE

Pool Control and Dosing Panel





- ABS Thermo-formed elegant panel
- Two ME2 -pH/Rx, electromagnetic dosing pumps with on-board pH/Rx controllers.
- Digital display for reading and programming.
- Easy programming and calibration, possible with just two buttons and a digital display.
- T.A.L. security system timed alarm for product end and electrode health testing system.

2 x PVC

Suction Tube

• Bath type electrode holder, with one 50 microns filter ahead.

2 x PE Injection

Tube 2mt

- Supplied assembled and ready for usage.
- Supplied complete with an installation kit.

INSTALLATION KIT

Standard

| Optional 2 x PP inj. Pyrex Ball valves with hastenoy spring | | | | | | | | | |
|---|---------------|-----------------|--------------|-------------|------|-----|-----------|---------------|--|
| TECHNICAL INFORMATION | | | | | | | | | |
| Туре | Lt/h pH-Rx | ml/min pH-Rx | Bar pH-Rx | lmp /min | Watt | VAC | Stroke | Tube Diam. | |
| 2-5 | 2-5 | 33 – 83 | 12 - 5 | 120 | 50 | 230 | 1,1 - 1,3 | 4x6 | |
| 5-8 | 5-8 | 83 – 133 | 5-2 | 120 | 50 | 230 | 1,3 - 1,3 | 4x6 | |
| | | | | | | | | | |

Power: 230VAC

Optional: • Other Flow-Rates on request


2 x PP Injection

VITON lip Valve


APPLICATIONS

Swimming pools

WEW



SIZE (mm)



| Component | Standard | Optional |
|-----------------------|-----------------|----------|
| Pump Head | PP 30% Talc re- | PVDF |
| | inforced | |
| Diaphragm | PTFE | |
| Double ball valve | 6mm Pyrex | |
| Injection fettings | PP | |
| Ball – O Ring | Pyrex - Viton | |
| Unon Reques | · | |

Injection Hastelloy spring Valves Viton/Dutral Lip-Valves PACKAGE (cm / Kg)

A B C KG

470 x 530 x 175

9 KG

NOTES

- MADE IN ITALY
- 100% Tested before delivery
- Produced conform to CE laws

2 x PP Foot

Filter

2 x PVC

Bleed Tube